

U.S. DEPARTMENT OF COMMERCE  
National Technical Information Service

AD-A034 112

A METHOD FOR THE NUMERICAL SOLUTION OF  
A PARTICULAR SET OF COUPLED ORDINARY  
DIFFERENTIAL EQUATIONS

NAVAL UNDERWATER SYSTEMS CENTER  
NEWPORT, RHODE ISLAND

7 DECEMBER 1976

ADA034112  
NUSC Technical Report 5383


011177

NUSC Technical Report 5383



# A Method for the Numerical Solution of a Particular Set of Coupled Ordinary Differential Equations

Gary T. Griffin  
Special Projects Department



7 December 1976

# NUSC

NAVAL UNDERWATER SYSTEMS CENTER  
Newport, Rhode Island • New London, Connecticut

Approved for public release; distribution unlimited.

REPRODUCED BY  
NATIONAL TECHNICAL  
INFORMATION SERVICE  
U. S. DEPARTMENT OF COMMERCE  
SPRINGFIELD, VA. 22161



## PREFACE

This report was prepared under the Ocean Measurements and Array Technology (OMAT) portion of the SEAGUARD Program sponsored by the Defense Advanced Research Projects Agency (ARPA Order No. 2976), Program Manager, R. Cook, Tactical Technology Office; NUSC Project No. A-696-70, Principal Investigator, G. Griffin (Code 311).

The Technical Reviewer for this report was Dr. Phillip B. Abraham (Code 313) and the author wishes to thank him for his assistance in the preparation of this report.

**REVIEWED AND APPROVED:** 7 December 1976

*H. O. Hass*

**R. W. Hasso**

**Head: Special Projects Dept.**

100-1107

BY  
DISTRIBUTION ZONE

Dial.

The author of this report is located at the New London Laboratory, Naval Underwater Systems Center, New London, Connecticut 06320.

| REPORT DOCUMENTATION PAGE   |  | READ INSTRUCTIONS<br>BEFORE COMPLETING FORM |
|---|--|---|
| 1. REPORT NUMBER<br>TR 5383   | 2. GOVT ACCESSION NO.  | 3. RECIPIENT'S CATALOG NUMBER               |
| 4. TITLE (and Subtitle)<br>A METHOD FOR THE NUMERICAL SOLUTION<br>OF A PARTICULAR SET OF COUPLED ORDINARY<br>DIFFERENTIAL EQUATIONS   | 5. TYPE OF REPORT & PERIOD COVERED                             |   |
|   | 6. PERFORMING ORG. REPORT NUMBER                               |   |
| 7. AUTHOR(s)<br>Gary T. Griffin   | 8. CONTRACT OR GRANT NUMBER(s)                                 |   |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS<br>Naval Underwater Systems Center<br>New London, CT 06320  | 10. PROGRAM ELEMENT, PROJECT, TASK<br>AREA & WORK UNIT NUMBERS |   |
| 11. CONTROLLING OFFICE NAME AND ADDRESS<br>Defense Advanced Research Projects Agency<br>1400 Wilson Blvd.<br>Arlington, VA 22209  | 12. REPORT DATE<br>7 December 1976                             |   |
|   | 13. NUMBER OF PAGES<br>17                                      |   |
| 14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)   | 15. SECURITY CLASS. (of this report)<br>UNCLASSIFIED           |   |
|   | 15a. DECLASSIFICATION/DOWNGRADING<br>SCHEDULE                  |   |
| 16. DISTRIBUTION STATEMENT (of this Report)<br><br>Approved for public release; distribution unlimited.   |  |   |
| 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)  |  |   |
| 18. SUPPLEMENTARY NOTES   |  |   |
| 19. KEY WORDS (Continue on reverse side if necessary and identify by block number)<br>Differential Equations<br>Hydrodynamic Mass<br>Nonlinear Differential Equations<br>Numerical Integration Techniques<br>Runge-Kutta Method   |  |   |
| 20. ABSTRACT (Continue on reverse side if necessary and identify by block number)<br>A method by which a particular set of coupled ordinary nonlinear differential equations may be solved numerically is presented. The nonlinearity is present due to the quadratic terms present in the derivatives. An example is given to illustrate the problem when applied to a model of a cable towed body moving through a viscous fluid. |  |   |



## TABLE OF CONTENTS

|  | Page |
|--|------|
| LIST OF SYMBOLS . . . . .                              | iii  |
| INTRODUCTION . . . . .                                 | 1    |
| PARTICULAR SET OF EQUATIONS . . . . .                  | 2    |
| A BRIEF BACKGROUND ON THE RUNGE-KUTTA METHOD . . . . . | 4    |
| SUMMARY . . . . .                                      | 8    |
| APPENDIX - HYDRODYNAMIC MASS . . . . .                 | 9    |
| REFERENCES . . . . .                                   | R-1  |

## LIST OF SYMBOLS

|                   |   |
|-------------------|---|
| $\vec{a}$         | Acceleration vector                           |
| A                 | Area  |
| A, B, C, D, and E | Square nonsingular coefficient matrices       |
| $C_1, C_2$        | Viscous force coefficient matrices            |
| D                 | Viscous force vector                          |
| $\vec{F}$         | Body force vector                             |
| G                 | Some general column vector                    |
| h                 | Time increment                                |
| H                 | Hydrodynamic force vector                     |
| J, K, L, M        | Square nonsingular coefficient matrices       |
| m                 | Mass  |
| $m_h$             | Hydrodynamic mass                             |
| $M_s$             | Structural mass matrix                        |
| $M_h$             | Hydrodynamic mass matrix                      |
| n                 | Direction index                               |
| $q_i$             | Displacement in the $i^{\text{th}}$ direction |
| Q                 | Displacement vector                           |
| S                 | Body surface                                  |
| t                 | Time  |
| T                 | Towline tension vector                        |
| u                 | Dummy variable = $\frac{dy}{dt}$              |
| v                 | Dummy variable = $\frac{dz}{dt}$              |
| $\phi$            | Normalized velocity potential                 |

A METHOD FOR THE NUMERICAL SOLUTION OF A  
PARTICULAR SET OF COUPLED ORDINARY  
NONLINEAR DIFFERENTIAL EQUATIONS

INTRODUCTION

The mathematical modeling of certain physical phenomena can be treated by many basic methods. Certain cases may lead to systems of nonlinear differential equations which can only be investigated by approximate methods. This paper discusses a system of equations of the form

$$A\ddot{Q} = BG - C\dot{Q}^2 - D\dot{Q} - EQ,$$

where  $A, B, C, D$  and  $E$  are square coefficient matrices and  $G, \dot{Q}, \ddot{Q}$  and  $\dot{Q}^2$  are column vectors. Here  $\dot{Q}^2$  is the column vector

$$\begin{bmatrix} \dot{q}_1^2 \\ \dot{q}_2^2 \\ \vdots \\ \dot{q}_n^2 \end{bmatrix}.$$

A method by which numerical solutions may be effected is also discussed.

## PARTICULAR SET OF EQUATIONS

Consider the system of differential equations written in matrix form as below,

$$A\ddot{Q} = BG - C\dot{Q}^2 - D\dot{Q} - EQ, \quad (1)$$

where the matrices and vectors are real and A is nonsingular.

If A is a square nonsingular matrix then it possesses an inverse,  $A^{-1}$ . Multiplying through by  $A^{-1}$  gives

$$\ddot{Q} = A^{-1}BG - A^{-1}C\dot{Q}^2 - A^{-1}D\dot{Q} - EQ \quad (2a)$$

or

$$\ddot{Q} = JG - K\dot{Q}^2 - L\dot{Q} - MQ, \quad (2b)$$

where

$$J = A^{-1}B$$

$$K = A^{-1}C$$

$$L = A^{-1}D$$

$$M = E.$$

If Q is a column vector of order n, then Q can be expressed as

$$Q = \begin{bmatrix} q_1 \\ q_2 \\ \cdot \\ \cdot \\ \cdot \\ q_n \end{bmatrix}, \quad (3)$$



and its time derivatives as

$$\dot{\mathbf{Q}} = \begin{bmatrix} \dot{q}_1 \\ \dot{q}_2 \\ \vdots \\ \dot{q}_n \end{bmatrix} \quad (4)$$

and

$$\ddot{\mathbf{Q}} = \begin{bmatrix} \ddot{q}_1 \\ \ddot{q}_2 \\ \vdots \\ \ddot{q}_n \end{bmatrix} \cdot \quad (5)$$

If A, B, C, D, and E are of (n x n) order, the matrix multiplication in (2a) will yield n ordinary coupled differential equations which are nonlinear due to the  $\dot{q}_i^2$  terms as shown below,

$$\ddot{q}_1 = f_1(t, q_1, q_2, \dots, q_n, \dot{q}_1, \dot{q}_2, \dots, \dot{q}_n, \dot{q}_1^2, \dots, \dot{q}_n^2) \quad (6a)$$

$$\ddot{q}_2 = f_2(t, q_1, q_2, \dots, q_n, \dot{q}_1, \dot{q}_2, \dots, \dot{q}_n, \dot{q}_1^2, \dot{q}_2^2, \dots, \dot{q}_n^2) \quad (6b)$$

$$\vdots$$

$$\ddot{q}_n = f_n(t, q_1, q_2, \dots, q_n, \dot{q}_1, \dot{q}_2, \dots, \dot{q}_n, \dot{q}_1^2, \dot{q}_2^2, \dots, \dot{q}_n^2) \quad (6c)$$

At the present time, a closed-form solution to these equations is not obtainable. It should be noted that for some physical problems, the coefficient matrices may possess time-dependent elements; if so, equations (6) become a set of nonautonomous, nonlinear, differential equations.

## A BRIEF BACKGROUND ON THE RUNGE-KUTTA METHOD

The solution of nonlinear differential equations in closed analytic form is not usually possible. The demands of applied science make it necessary to obtain some insight into the nature of solutions subject to given boundary conditions. Graphical and numerical representation of the functions are the usual methods employed.<sup>1</sup>

The numerical solution of differential equations by a method of finite integration in one of its several forms is a favorite tool when performed by means of digital computers. The Runge-Kutta method is used perhaps more than any other, and will be reviewed here briefly.<sup>2</sup>

Consider a system of first-order simultaneous differential equations. For simplicity, choose two as given below (note that the method can be extended to  $n$  equations).

$$\frac{dy}{dt} = f(t, y, z) \quad (7)$$

$$\frac{dz}{dt} = g(t, y, z).$$

The estimate for the function  $y$  and  $z$  at some later time  $(t + h)$  can be computed by the relations

$$y(t) = y_0 + \Delta y = y_0 + 1/6 (\Delta'z + 2\Delta''y + 2\Delta'''y + \Delta^4y) \quad (8)$$

and

$$z(t) = z_0 + \Delta z = z_0 + 1/6 (\Delta'y + 2\Delta''z + 2\Delta'''z + \Delta^4z).$$

The increment values  $(\Delta^i)$  are computed from:

$$\Delta'y = f(t_0, y_0, z_0) h \quad (9)$$

$$\Delta'z = g(t_0, y_0, z_0) h$$

$$\Delta''y = f(t_0 + 1/2h, y_0 + 1/2 \Delta'y, z_0 + 1/2 \Delta'z) h \quad (10)$$

$$\Delta''z = g(t_0 + 1/2h, y_0 + 1/2 \Delta'y, z_0 + 1/2 \Delta'z) h$$

$$\Delta''y = f(t_0 + 1/2h, y_0 + 1/2 \Delta''y_0, z_0 + 1/2 \Delta''z) h \quad (11)$$

$$\Delta''z = g(t_0 + 1/2h, y_0 + 1/2 \Delta''y, z_0 + 1/2 \Delta''z) h$$

$$\Delta^4y = f(t_0 + h, y_0 + \Delta''y, z_0 + \Delta''z) h \quad (12)$$

$$\Delta^4z = g(t_0 + h, y_0 + \Delta''y, z_0 + \Delta''z) h.$$

If the increments of  $y$  and  $z$  are computed in the order given, only the previously computed increments are needed in each step in the computation (i.e., the increments cannot be computed simultaneously).

This method can be applied to a system of higher-order equations without essential change. Consider the system of second-order equations

$$\frac{d^2y}{dt^2} = f(t, y, z, \frac{dy}{dt}, \frac{dz}{dt}) \quad (13)$$

and

$$\frac{d^2z}{dt^2} = g(t, y, z, \frac{dy}{dt}, \frac{dz}{dt}).$$

Introducing the new variables

$$u = \frac{dy}{dt} \text{ and } v = \frac{dz}{dt}, \quad (14)$$

the system of equations given by (13) becomes

$$\frac{du}{dt} = f(t, y, z, u, v)$$

and

$$\frac{dv}{dt} = g(t, y, z, u, v). \quad (15)$$

This system of equations can now be numerically integrated, using the method described earlier.

Consider the system of equations given in (6) earlier. The Runge-Kutta integration method requires that the



highest-order derivative of only one dependent variable be on the left side of the equality in each equation, since the estimate of each function (see equations (9) through (12)) is computed in a stepwise fashion, using the increment values  $\Delta^i$ . An attempt to numerically integrate a system of equations with more than one highest-order derivative on either side of the equality will make the Runge-Kutta algorithm unstable. The set of equations given in (6) are now of a form which is acceptable to the Runge-Kutta algorithm.

Note that the elements of the coefficient matrices may be time-dependent. If so, they can be computed at each time increment before the matrix operations take place. Most digital computers are equipped with built-in subroutines for the evaluation of matrices and determinants. These can be incorporated within the numerical integration loop as the integration is carried on.

#### EXAMPLE

Consider the equation of motion of a towed body moving through a nonaccelerating viscous fluid.<sup>3,4</sup> In body coordinates, the equations become, in matrix form,

$$M_S \ddot{Q} - M_S G + H + T = 0, \quad (16)$$

where

- $M_S$  = the body structural mass matrix
- $Q$  = the displacement vector of the body
- $G$  = the gravitational vector
- $H$  = the hydrodynamic force vector
- $T$  = the towline tension vector.

The hydrodynamic force vector (from boundary layer theory<sup>5</sup>) can be written as

$$H = M_h \ddot{Q} + D, \quad (17)$$

where

- $M_h$  = the body hydrodynamic mass matrix
- =  $m_{hij}$  (see appendix)
- $D$  = the viscous force vector.

Substituting (17) into (16) gives

$$(M_S + M_h) \ddot{Q} = MG - D - T. \quad (18)$$

If the viscous force vector is considered to be given in the form

$$D = C_1 \dot{Q}^2 + C_2 \dot{Q}, \quad (19)$$

where  $C_1$  and  $C_2$  are viscous coefficient (i.e., lift, drag, linear-damping coefficients or stability derivatives) matrices for the body in question, substitution into (12) gives

$$(M_S + M_h) \ddot{Q} = M_S G - C_1 \dot{Q}^2 - C_2 \dot{Q} - T, \quad (19)$$

which is of the same form as (1) discussed previously.

For a body with six degrees of freedom, there are  $6 \times 2 = 12$  equations which describe the body motion (i.e., acceleration and velocity) and the necessary auxiliary relations which must be found to compute the towline tension.<sup>3,4</sup>

Using the method described in the first section, these equations can be numerically integrated when put into the form as given by (6). Note that the elements of the hydrodynamic mass matrix may be time- or amplitude-dependent.<sup>6,7</sup> For this case, they can be recomputed at the end of each time increment in the numerical integration before the matrix operations in (2) are performed.

SUMMARY

It has been noted that a particular set of nonlinear differential equations may be reduced to a form such that numerical integration of the equations may be effected using a Runge-Kutta method. One example of a physical system to which a set of equations of this form may apply has been provided to illustrate the problem. It is the intent of this paper to point out one approximate method of solution to these equations as an aid to anyone confronted by a similar problem.



## APPENDIX

## HYDRODYNAMIC MASS

For the case of a body moving through a fluid, the effects on body motions due to hydrodynamic inertia (or hydrodynamic mass) terms must sometimes be accounted for by the mathematical model used. For a body moving in an unsteady manner, the fluid disturbance due to the body motion extends in decreasing amplitude to infinity. From a system of reference moving with the body, the effect can be considered as localized to a finite volume of fluid surrounding the body. The body acts as if an added mass of fluid is moving with it. If the body is subjected to an acceleration, not only must the body mass be accelerated but also the added mass of fluid.<sup>8</sup>

Writing Newton's Second Law for the body gives

$$F = (m + m_h) \vec{a}.$$

Here  $m$  is the mass of the body and  $m_h$  is the added mass or hydrodynamic mass of the body.

The hydrodynamic mass is expected to be proportional to the fluid density, body size (i.e., its volume), and its orientation while in motion through the fluid. For general body cases with six motion degrees of freedom, there are 21 hydrodynamic inertia components.<sup>6</sup> These are best given in the form of a symmetric tensor. Specifically,

$$m_{hij} = -\rho \int \frac{\partial \phi_i}{\partial n} \phi_j dA \quad \begin{matrix} i = 1, 2, 3, \dots, 6 \\ j = 1, 2, 3, \dots, 6, \end{matrix}$$

where  $\phi_j$  is the normalized velocity potential caused by a unit motion from some reference position, and it can be shown that the various  $\frac{\partial \phi_i}{\partial n}$  depend only on body shape.<sup>6,8</sup>

Miller<sup>9</sup> has shown that the hydrodynamic mass values may be both frequency and amplitude dependent for irregular shaped bodies. For this condition, the set of differential equations used to model the body motion become nonautonomous. The techniques described in the body of the report

may be useful in obtaining approximate solutions to the types of equations used to model this problem.

The effects of hydrodynamic inertia terms on some physical systems may be significant and should be considered when writing equations of motion for such systems. If they are determined to be negligible as applied to a particular system, they should, by all means, be neglected in order to effect solutions. However, in the case of certain body motions in a viscous fluid, the equations of motion may become highly nonlinear due to the effects of damping and hydrodynamic inertia. For this case, numerical methods of solution may be required.

## REFERENCES

1. Harold T. Davis, Introduction to Nonlinear Differential and Integral Equations, Dover Publications, Inc., New York, 1962.
2. Kaiser S. Kunz, Numerical Analysis, McGraw Hill Book Company, New York, 1957.
3. Gary T. Griffin, "Dynamics of a Cable-Towed Body System," MS Thesis, University of Rhode Island, Kingston, Rhode Island, 1974.
4. K. T. Patton, "The Response of Cable-Moored Axisymmetric Buoys to Ocean Wave Excitation," Ph.D Dissertation, University of Rhode Island, Kingston, Rhode Island, 1972.
5. Hermann Schlichting, Boundary Layer Theory, McGraw-Hill Book Company, Inc., New York, 1955.
6. Garrett Birkoff, Hydrodynamics, Princeton University Press, 1950.
7. James M. Robertson, Hydrodynamics in Theory and Application, Prentice-Hall, Inc., New Jersey, 1965.
8. Kirk T. Patton, "Tables of Hydrodynamic Mass Factors for Translational Motion," ASME Paper 65-WA/UNT-2, The American Society of Mechanical Engineers, New York, 1965.
9. R. R. Miller, "The Effects of Frequency and Amplitude of Oscillation on the Hydrodynamic Mass of Irregular Shaped Bodies," MS Thesis, University of Rhode Island, Kingston, Rhode Island, 1965.